To fix the remote, two options are offered for selection:

fix the remote' back holder on the wall with two screws.

adhere the remote' back holder to the wall with paster.

Ultrathin Touch Wheel RF Remote Controller

Model No.: R8/R8-1

1 and 4 zone RGB or RGBW/Touch color wheel/Wireless remote 30m distance/CR2032 battery

• • •

R8

4 Zone RGB/RGBW

1 2 3 4

Features

- Apply to RGB or RGBW LED controller.
- Ultra sensitive color adjustment touch wheel.
- Each remote can match one or more receiver.
- CR2032 battery powered.
- Operate with LED indicator light.

Technical Parameters

	Input and Output		Safety c
	Output signal	RF(2.4GHz)	EMC stan
	Working voltage	3VDC(CR2032)	
	Working current	< 5mA	Safety sta
	Standby current	< 10µA	Radio Equ
	Standby time	l year	Certificati
	Remote distance	30m(Barrier-free space)	Warran
	Environment		Warrant
	Operation temperature	Ta: -30°C ~ +55°C	Weight
	IP rating	IP20	Net weig

Safety and EMC			
EMC standard (EMC)	ETSI EN 301 489-1 V2.2.3 ETSI EN 301 489-17 V3.2.4		
Safety standard(LVD)	EN 62368-1:2020+A11:2020		
Radio Equipment(RED)	ETSI EN 300 328 V2.2.2		
Certification	CE,EMC,IVD,RED		
Warranty			
Warranty	5 years		
Weight			
Net weight	0.037kg		
Gross weight	0.062kg		

0


B G B M

R8-


1 Zone RGB/RGBW

CE RoHS emc LVD RED

Mechanical Structures and Installations








Note: Before the first use, please remove the protective film on the battery.

Note: If the LED indicator is not on when press key, it is due to dead battery or bad contact caused by multiple plugging, please replace the battery, or raise the battery shrapnel with a screwdriver.



Operation

- When light is on, touch the color wheel, the indicator will display red.
- To extend battery life, no touch or press key operation after a few seconds, the touch wheel will enter sleep state, you need press any key to make touch wheel quit sleep state.

Match Remote Control (two match ways)

End user can choose the suitable match/delete ways. Two options are offered for selection:

Use the controller's Match key

Match:

Short press match key, immediately press on/off key (single zone remote) or zone key (multiple zone remote) on the remote.

The LED indicator fast flash a few times means match is successful.

Delete:

Press and hold match key for 5s to delete all match, The LED indicator fast flash a few times means all matched remotes were deleted.

Use Power Restart

Option 1:


Option 2

Match:

Switch off the power, then switch on power, repeat again Immediately short press on/off key (single zone remote) or zone key (multiple zone remote) 3 times on the remote. The light blinks 3 times means match is successful.

Delete:

Switch off the power, then switch on power, repeat again. Immediately short press on/off key (single zone remote) or zone key (multiple zone remote) 5 times on the remote. The light blinks 5 times means all matched remotes were deleted.



1,2,3,4 zone: Short press select and turn on zone light, long press 2s turn off zone light. Short press multiple zone key fastly, will synchronous select multiple zone synchronously. Color wheel: Touch to change current zone static RGB color.

Mode: Short press run the next dynamic mode, long press 2s run mode cycle.

Bright+/-: Static color, adjust brightness,

short press 10 levels, long press 1-6s for continuous 256 levels adjustment.

Speed+/-: Dynamic mode, adjust speed,

short press 10 levels, long press 2s get the fastest or slowest speed.

W: For RGB light, short press turn on/off white (RGB mix), long press 1-6s adjust saturation continuously, namely change current static RGB color to mixed white slowly.

For RGBW light, short press turn on/off W channel, long press 1-6s adjust W brightness continuously.

Scene: Short press recall the scene, long press 2s save.

the LED indicator will light up longer when save OK.

4 zone recall or save synchronously.



On/Off: Turn on/off light.

Color wheel: Touch to change static RGB color.

Mode: Short press run the next dynamic mode, long press 2s run mode cycle.

Speed/Saturation: For dynamic mode, adjust speed, short press 10 levels, long press 2s get the default speed. For static color, adjust saturation, namely change current static RGB color to mixed white slowly, short press 11 levels, long press 1-6s for continuous 256 levels adjustment. Bright+/: Adjust brightness, short press 10 levels, long press 1-6s for continuous 256 levels adjustment. R/G/B: Short press get red, green or blue color directly, long press 1-6s adjust R/G/B brightness continuously to achieve millions of colors. W+/: For RGB light, short press turn on/off white[RGB mix], long press 1-6s adjust saturation continuously, namely change current static RGB color to mixed while slowly. For RGBW light, short press turn on/off W channel, long press 1-6s adjust W brightness continuously. Scene: Short press recall the scene, long press 2 s save the current color into the scene. the LED indicator will light up longer when save OK.

Safety information

- 1. Read all instructions carefully before you begin this installation.
- When installing battery, pay attention to the battery positive and negative polarity. A long time without the remote control, remove the battery. When remote distance becomes smaller and insensitive, replace the battery.
- 3. If no response from the receiver, please re-match the remote.
- 4. Gently handle remote, beware of falling.
- 5. For indoor and dry location use only.