A1 / 07.



## **Attestation of Conformity**

No. N8A 18 05 04287 001

Holder of Certificate: **Guangzhou Linong Lighting** 

Technology Co., Ltd.

Keying Road, Guangzhou Sci-Tech Industry Park, Taihe Town

Baiyun District

510540 Guangzhou City, Guangdong Province

PEOPLE'S REPUBLIC OF CHINA

Product: Lighting chain

(LED Strip Light)

Model(s): **LNTS Series** 

(See page 2 for details of model description)

Parameters: Rated Voltage: 100-240VAC or 220-240VAC

(for LED driver);

12VDC (for LED strip light) Rated Frequency: 50/60Hz (for LED driver) Rated Power: See page 2 for details Protection Class:

II (for LED driver) III (for LED strip light)

Degree of Protection: **IP20** Blue Light Risk Group: RG1

Tested according to:

EN 60598-2-21:2015 EN 60598-1:2015 EN 62493:2015

This Attestation of Conformity is issued on a voluntary basis according to the Low Voltage Directive 2014/35/EU relating to electrical equipment designed for use within certain voltage limits. It confirms that the listed equipment complies with the principal protection requirements of the directive and is based on the technical specifications applicable at the time of issuance. It refers only to the particular sample submitted for testing and certification. See also notes overleaf.

Test report no.:

6814017113101





After preparation of the necessary technical documentation as well as the EU declaration of conformity the required CE marking can be affixed on the product. The declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.

Page 1 of 2



## ZERTIFIKAT

## **Attestation of Conformity** No. N8A 18 05 04287 001



Model No.	Rated Power (W) (Z=1, 2, 3, 4, 5, 6, 7, 8, 9 or 0)										Remark
	1	2	3	4	5	6	7	8	9	0	Nemark
LNTS3XX30YZ-D12	1.2	2.4	3.5	4.6	5.6	6.8	7.9	9.2	10.8	12	
LNTS3XX60YZ-D12	2.4	4.8	7.2	9.2	10.8	12.2	13.2	16.8	17.4	18	"XX" = WW, NW, PW, CW, RR, GG, BB, YY or RB
LNTS3XX120YZ-D12	4.8	9.6	14.4	18.6	22.5	26.6	29	32.6	34	36	
LNTS3XX180YZ-D12	5.6	11.5	16	21.2	25	30.2	33	36.2	38	42	
LNTS3XX240YZ-D12	7.2	14.4	20	26.4	31	35.8	38	42	45	48	
LNTS5XX30YZ-D12	3.6	7.2	9.6	12	13.5	15	16.5	18	20	22	"XX" = WW, NW, PW,
LNTS5XX60YZ-D12	7.2	14.4	19.2	24	27	30	33	36	39	42	CW, RR, GG, BB, YY, DW, TC or FC
LNTS8XX30YZ-D12	1.8	3.6	5.2	6.8	8.8	10.8	12	13.2	14.6	16	"XX" = WW, NW, PW, CW, RR, GG, BB or YY
LNTS8XX60YZ-D12	3.6	7.2	9.6	12	13.5	15	16.5	18	20	22	
LNTS8XX120YZ-D12	7.2	14.4	19.2	24	27	30	33	36	39	42	

## Remark:

"XX"= WW, NW, PW, CW, RR, GG, BB, YY, RB, DW, TC or FC, indicates color of LED, WW=3000K White, NW=4000K White, PW=6000K White, CW=11000K White, RR=Red, GG=Green, BB=Blue, YY=Yellow, RB=Red+Blue, DW=Double White, TC=Red+Green+Blue, FC=Red+Green+Blue+White.

"Y"= N, G, U or Q, indicates package type of LED strip, N=Non coating, G=Silicone glue coating, U=U-shape tube with silicone glue inside, Q=Silicon tube.

"Z"=1, 2, 3, 4, 5, 6, 7, 8, 9 or 0, indicates length of LED strip, 1=0.5m/strip, 2=1m/strip, 3=1.5m/strip, 4=2m/strip, 5=2.5m/strip, 6=3m/strip, 7=3.5m/strip, 8=4m/strip, 9=4.5m/strip, 0=5m/strip.