

No. N5A 004287 0006 Rev. 00

Holder of Attestation: Guangzhou Linong Lighting

Technology Co., Ltd.

Room 115, 1st Floor, Building 3

minjie Science and Technology Innovation

Center, No. 3, Kerong Street

Guangzhou Private Science and Technology

Park, No. 1633 Beitai Road

Baiyun District 510540 Guangzhou

PEOPLE'S RÉPUBLIC OF CHINA

Product: Fixed general purpose luminaires

(LED strip light)

This Attestation of Compliance is issued on a voluntary basis according to Chapter II of the General Product Safety Regulation (EU) 2023/988 relating to electrical equipment where no specific provisions with the safety objective under Union law or the risks or categories of risks not covered by Union harmonization legislation. It confirms that the listed equipment complies with the principal protection requirements of the regulation and is based on the technical specifications applicable at the time of issuance. It refers only to the sample submitted for conformity assessment. For details see: www.tuvsud.com/ps-cert

**Test report no.:** 6814024073401

**Date**, 2025-01-09

(Taylor Yao)





No. N5A 004287 0006 Rev. 00

Model(s):

LNTS3I240XZ-D12; LNTS3I120XZ-D12; LNTS3I60XZ-D12; LNTS4I96XZ-D12; LNTS4I60XZ-D12; LNTS5I120XZ-D12; LNTS5I60XZ-D12; LNTKD5I144XZ-D12; LNTKD5I60XZ-D12; LNTS6I300XZ-D12; LNTS6I240XZ-D12; LNTS6I120XZ-D12; LNTS7I144XZ-D12; LNTS7I120XZ-D12; LNTS8I240XZ-D12; LNTS8I192XZ-D12; LNTS8I168XZ-D12; LNTS8I120XZ-D12; LNTS8I60XZ-D12; LNTKD8I126XZ-D12; LNTKD8I72XZ-D12; LNTS0I608XZ-D12; LNTS0I480XZ-D12; LNTS0I384XZ-D12; LNTKD0I720XZ-D12; LNTKD0I576XZ-D12; LNTS3I240XZ-D24; LNTS3I120XZ-D24; LNTS3I60XZ-D24; LNTS4I96XZ-D24; LNTS4I60XZ-D24; LNTS5I120XZ-D24; LNTS5I60XZ-D24; LNTKD5I80XZ-D24; LNTKD5I60XZ-D24; LNTS6I300XZ-D24; LNTS6I240XZ-D24; LNTS7I144XZ-D24; LNTS7I120XZ-D24; LNTS8I240XZ-D24; LNTS8I192XZ-D24; LNTS8I168XZ-D24; LNTS8I120XZ-D24; LNTS8I60XZ-D24; LNTKD8I126XZ-D24; LNTKD8I84XZ-D24; LNTS0I608XZ-D24; LNTS0I480XZ-D24; LNTS0I384XZ-D24; LNTKD0I720XZ-D24; LNTKD0I576XZ-D24 ('I' can be WNW, WW, CW, NW, PW, W, R, G, B, Y, RGB, RGBW, RBGWNW, denotes color of LED light, WNW=white+nature white, WW=warm white, CW=cool white, NW=nature white, PW=pure white, W=white, R=red, G=green, B=blue, Y=yellow, RGB=red+green+blue, RGBW= red+green+blue+white, RGBWNW= red+green+blue+white+nature white; 'X' can be N, H, J, V, U, T, E or G, denotes protection type of LED strip, N=Non coating, H=silicon extrusion (not fill in silicon), J=PU glue coating, V= silicon extrusion (fill in silicon), U=U type silicon coating, T=silicon spraying, E=silicon hollow tube, G=semi-circular shape silicon coating; 'Z' can be 1, 2, 3, 4, 5, 6, 7, 8, 9 or 0, denotes length of LED strip, 1=0.5m, 2=1m, 3=1.5m, 4=2m, 5=2.5m, 6=3m, 7=3.5m, 8=4m, 9=4.5m, 0=5m.)

Page 2 of 6



No. N5A 004287 0006 Rev. 00

Brand: LNLED



#### **Parameters:**

Rated Voltage: See below table for details Rated Power: See below table for details

Protection Class: III
Degree of Protection: IP20
Blue Light Risk Group: RG1

**Tested** EN IEC 60598-2-1:2021

**according to:** EN IEC 60598-1:2021/A11:2022 EN 62493:2015/A1:2022





No. N5A 004287 0006 Rev. 00

Model No.	Rated Voltage (VDC)	Rated Power (W) (Z=1, 2, 3, 4, 5, 6, 7, 8, 9 or 0)									
		1	2	3	4	5	6	7	8	9	0
LNTS3I240XZ-D12	12	9.5	18.5	27.2	30.3	37.3	40.7	43.6	45.6	47.6	49.2
LNTS3I120XZ-D12	12	4.8	9.6	14.4	18.6	22.5	26.6	29.0	32.6	34.0	36.0
LNTS3I60XZ-D12	12	2.4	4.8	7.2	9.2	10.8	12.2	13.2	16.8	17.4	18.0
LNTS4I96XZ-D12	12	7.2	14.0	19.6	25.4	30.1	35.5	39.2	44.3	48.4	53.3
LNTS4I60XZ-D12	12	6.2	12.1	16.9	21.9	25.9	30.6	33.8	38.2	41.7	45.9
LNTS5I120XZ-D12	12	11.5	22.4	33.0	36.7	45.1	49.3	52.8	55.2	57.6	59.5
LNTS5I60XZ-D12	12	7.2	14.4	19.2	24.0	27.0	30.0	33.0	36.0	39.0	42.0
LNTKD5I144XZ-D12	12	7.0	13.3	19.5	25.8	31.5	37.4	41.7	46.5	49.8	52.5
LNTKD5l60XZ-D12	12	4.8	9.6	14.4	18.6	22.5	26.6	29.0	32.6	34.0	36.0
LNTS6I300XZ-D12	12	10.5	20.4	30.1	33.5	41.2	45.0	48.2	50.4	52.6	54.4
LNTS6I240XZ-D12	12	8.3	16.1	23.8	26.5	32.6	35.6	38.1	39.8	41.6	43.0
LNTS6I120XZ-D12	12	4.7	9.2	13.4	17.3	20.2	23.0	25.3	27.5	28.8	30.1
LNTS7I144XZ-D12	12	13.0	25.3	37.3	41.5	51.0	55.8	59.7	62.4	65.1	67.3
LNTS7I120XZ-D12	12	12.2	23.7	34.8	38.9	47.9	52.3	56.0	58.6	61.1	63.2
LNTS8I240XZ-D12	12	13.6	26.4	39.0	43.4	53.3	58.3	62.4	65.3	68.2	70.4
LNTS8I192XZ-D12	12	12.5	24.3	35.8	39.9	49.1	53.6	57.4	60.0	62.6	64.8
LNTS8I168XZ-D12	12	10.6	20.5	30.2	33.5	41.2	45.0	48.2	50.4	52.7	54.5
LNTS8I120XZ-D12	12	7.2	14.4	19.2	24.0	27.0	30.0	33.0	36.0	39.0	42.0

Page 4 of 6





No. N5A 004287 0006 Rev. 00

LNTS8I60XZ-D12	12	3.6	7.2	9.6	12.0	13.5	15.0	16.5	18.0	20.0	22.0
LNTKD8I126XZ-D12	12	4.5	8.8	12.6	16.6	20.3	23.0	25.5	28.1	29.2	30.6
LNTKD8I72XZ-D12	12	2.6	5.1	7.1	9.2	10.9	12.8	14.2	16.0	17.5	19.3
LNTS0I608XZ-D12	12	7.3	13.9	19.7	24.8	28.5	31.5	33.7	34.5	32.9	35.0
LNTS0I480XZ-D12	12	5.8	11.4	16.5	21.3	24.9	28.4	31.3	33.9	35.5	37.1
LNTS0I384XZ-D12	12	5.2	10.1	14.9	16.6	20.4	22.3	23.9	25.0	26.1	26.9
LNTKD0I720XZ-D12	12	7.0	13.3	19.5	25.8	31.5	37.4	41.7	46.5	49.8	52.5
LNTKD0I576XZ-D12	12	5.3	10.3	14.4	18.7	22.2	26.1	28.9	32.6	35.6	39.2
LNTS3I240XZ-D24	24	9.5	18.6	27.1	35.0	42.8	50.7	58.5	65.4	71.8	77.0
LNTS3I120XZ-D24	24	4.9	9.6	14.3	18.9	23.4	27.9	32.1	36.1	39.5	42.7
LNTS3I60XZ-D24	24	2.4	4.8	7.1	9.5	11.7	13.9	16.0	18.1	19.8	21.3
LNTS4I96XZ-D24	24	7.2	14.3	21.0	27.1	32.8	38.9	44.4	49.5	54.4	59.0
LNTS4I60XZ-D24	24	6.2	12.1	17.9	23.5	29.2	34.7	39.8	44.3	48.7	52.3
LNTS5I120XZ-D24	24	11.5	22.5	32.8	42.3	51.8	61.4	70.8	79.1	86.9	93.2
LNTS5I60XZ-D24	24	7.1	14.2	20.9	27.0	32.6	38.7	44.3	49.4	54.2	58.9
LNTKD5I80XZ-D24	24	13.0	25.9	37.1	47.8	58.5	69.4	80.1	89.4	98.3	105.3
LNTKD5I60XZ-D24	24	9.0	17.6	26.2	34.4	42.8	50.8	58.3	64.8	71.3	76.5
LNTS6I300XZ-D24	24	10.5	20.6	29.9	38.6	47.3	56.1	64.7	72.2	79.4	85.1
LNTS6I240XZ-D24	24	8.3	16.3	24.2	31.7	39.4	46.8	53.7	59.8	65.7	70.6
LNTS7I144XZ-D24	24	13.0	25.9	37.1	47.8	58.5	69.4	80.1	89.4	98.3	105.3

Page 5 of 6



No. N5A 004287 0006 Rev. 00

LNTS7I120XZ-D24	24	12.3	24.0	35.3	46.1	56.4	66.2	75.5	84.3	92.6	101.1
LNTS8I240XZ-D24	24	15.8	31.5	42.5	52.7	63.8	75.1	83.3	92.6	100.0	105.3
LNTS8I192XZ-D24	24	11.0	21.6	31.7	41.4	50.6	59.4	67.8	75.7	83.2	90.8
LNTS8I168XZ-D24	24	10.5	20.6	30.6	40.1	49.9	59.2	68.0	75.6	83.2	89.3
LNTS8I120XZ-D24	24	7.5	14.7	21.8	29.0	35.6	42.3	48.6	54.6	60.1	65.3
LNTS8I60XZ-D24	24	4.3	8.5	12.6	16.8	20.8	24.7	28.4	32.0	35.0	37.8
LNTKD8I126XZ-D24	24	4.5	8.9	13.1	16.9	20.5	24.3	27.7	31.0	34.0	36.9
LNTKD8I84XZ-D24	24	3.1	6.1	9.0	11.8	14.7	17.5	20.1	22.3	24.6	26.4
LNTS0I608XZ-D24	24	7.3	14.3	20.8	26.9	32.9	39.0	43.4	48.5	51.9	54.8
LNTS0I480XZ-D24	24	6.0	11.7	16.3	21.2	25.1	29.6	32.7	36.9	40.3	44.4
LNTS0l384XZ-D24	24	5.4	10.5	14.7	19.1	22.6	26.6	29.4	33.2	36.3	40.0
LNTKD0I720XZ-D24	24	11.2	21.8	32.1	43.5	53.5	62.5	72.7	81.7	89.5	95.5
LNTKD0I576XZ-D24	24	8.5	16.5	23.1	23.0	35.5	41.9	46.3	52.3	57.1	62.9